



**Specifications Noxion LED Panel Delta Pro V5 28W 3700lm - 830 Warm White | 120x30cm - UGR <19 - Sidelit - TRIAC Dimmable**

[View Product](#)

## General Information

|                          |   |
|--------------------------|---|
| SKU                      | 257843  |
| EAN                      | 8719157073783   |
| Brand                    | Noxion  |
| Manufacturer Name        | Noxion LED Panel Delta Pro V5.1 28W 3700lm 3000K 300*1200 UGR<19 Sidelit - TRIAC dimmable NDL |
| Any Lamp all-in warranty | 6 Years   |
| Average Lifetime (h)     | 100000  |
| Series                   | Delta Pro   |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Technology                  | LED Integrated    |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Luminous Efficacy (lm/W)    | 132               |
| IP-rating                   | IP20              |
| Impact Protection (IK)      | IK02 - 0.20 joule |

|                    |               |
|--------------------|---------------|
| Fixture Connection | Push Terminal |
|--------------------|---------------|

|                     |         |
|---------------------|---------|
| Finish of Reflector | Frosted |
|---------------------|---------|

|              |       |
|--------------|-------|
| Power factor | >0.90 |
|--------------|-------|

|                       |           |
|-----------------------|-----------|
| Product Type Category | LED Panel |
|-----------------------|-----------|

## Fixture Information

|                 |          |
|-----------------|----------|
| Mounting Method | Recessed |
|-----------------|----------|

|                      |                                |
|----------------------|--------------------------------|
| Unified Glare Rating | < 19 - for offices and schools |
|----------------------|--------------------------------|

|               |                  |
|---------------|------------------|
| Optical Cover | PS (Polystyrene) |
|---------------|------------------|

|                       |            |
|-----------------------|------------|
| Operating Temperature | -20 to +40 |
|-----------------------|------------|

|                    |                   |
|--------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
|--------------------|-------------------|

|                       |       |
|-----------------------|-------|
| Colour of the Fixture | White |
|-----------------------|-------|

|         |       |
|---------|-------|
| Housing | Steel |
|---------|-------|

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
|----------------|----------|

|             |      |
|-------------|------|
| Length (mm) | 1195 |
|-------------|------|

|            |     |
|------------|-----|
| Width (mm) | 295 |
|------------|-----|

|             |    |
|-------------|----|
| Height (mm) | 10 |
|-------------|----|

## Sensor Information

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

**Why Any-lamp?**

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process