



Specifications Philips LED Panel  
RC132V CoreLine G5 Steel White 34W  
3600lm - 840 Cool White | 120x30cm -  
UGR < 22 - Emergency 3H

[View Product](#)

## General Information

|                          |  |
|--------------------------|--|
| SKU                      | 246310                                 |
| EAN                      | 8720169013759                          |
| Brand                    | Philips                                |
| Manufacturer Name        | RC132V G5 36S/840 PSU W30L120 NOC ELB3 |
| Any Lamp all-in warranty | 5 Years                                |
| Average Lifetime (h)     | 50000                                  |
| Series                   | RC132V                                 |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Including bulb              | Yes             |
| Amount of bulbs required    | 1               |
| Luminous Efficacy (lm/W)    | 106             |

|                        |                               |
|------------------------|-------------------------------|
| IP-rating              | IP20                          |
| Impact Protection (IK) | IK03 - 0.35 joule             |
| Fixture Connection     | PI [Push-in connector 3-pole] |
| Finish of Reflector    | Acrylate                      |
| Power factor           | >0.90                         |
| Product Type Category  | LED Panel                     |

## Fixture Information

|                       |                          |
|-----------------------|--------------------------|
| EOC8                  | 01375900                 |
| Mounting Method       | Recessed                 |
| Unified Glare Rating  | < 22 - for general areas |
| Optical Cover         | PS (Polystyrene)         |
| Operating Temperature | 0 to +35                 |
| Emergency Lighting    | With Emergency Unit      |
| Colour of the Fixture | White                    |
| Housing               | Steel                    |
| Colour of material    | White                    |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1195     |
| Width (mm)     | 295      |
| Height (mm)    | 69       |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process