



Specifications Philips LED Panel  
CoreLine RC136B G4 38.5W 6000lm -  
840 Cool White | 60x60cm - UGR<19

[View Product](#)

## General Information

|                          |                                       |
|--------------------------|---------------------------------------|
| SKU                      | 253373                                |
| EAN                      | 8720169764163                         |
| Brand                    | Philips                               |
| Manufacturer Name        | RC136B G4 36_45_60S/840 PSU W60L60 OC |
| Any Lamp all-in warranty | 5 Years                               |
| Average Lifetime (h)     | 100000                                |
| Series                   | CoreLine                              |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Technology                  | LED Integrated    |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Luminous Efficacy (lm/W)    | 155.8             |
| IP-rating                   | IP20/IP44         |
| Impact Protection (IK)      | IK03 - 0.35 joule |

|                    |                               |
|--------------------|-------------------------------|
| Fixture Connection | PI [Push-in connector 3-pole] |
|--------------------|-------------------------------|

|              |       |
|--------------|-------|
| Power factor | >0.90 |
|--------------|-------|

|                       |           |
|-----------------------|-----------|
| Product Type Category | LED Panel |
|-----------------------|-----------|

## Fixture Information

|                 |          |
|-----------------|----------|
| Mounting Method | Recessed |
|-----------------|----------|

|                      |                                |
|----------------------|--------------------------------|
| Unified Glare Rating | < 19 - for offices and schools |
|----------------------|--------------------------------|

|               |                    |
|---------------|--------------------|
| Optical Cover | PC (Polycarbonate) |
|---------------|--------------------|

|                       |            |
|-----------------------|------------|
| Operating Temperature | -10 to +40 |
|-----------------------|------------|

|                    |                   |
|--------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
|--------------------|-------------------|

|                       |       |
|-----------------------|-------|
| Colour of the Fixture | White |
|-----------------------|-------|

|         |       |
|---------|-------|
| Housing | Steel |
|---------|-------|

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
|----------------|---------|

|             |     |
|-------------|-----|
| Length (mm) | 595 |
|-------------|-----|

|            |     |
|------------|-----|
| Width (mm) | 595 |
|------------|-----|

|             |    |
|-------------|----|
| Height (mm) | 38 |
|-------------|----|

## Sensor Information

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

## Why Any-lamp?

 Order from the **largest lighting specialist** in Europe  **Customised** quotation

 Up to **7 years warranty**  **Easy** return process